

Burglaryproof PK-400 data safes

EN 14450 Grade S1 (ECB-S)
NT Fire 017 – 120 Diskette

Locking and security

- Four-way locking mechanism consists of sliding locking bolts on three sides and a locking frame structure on the back panel of the door
- PK-400 data safes are supplied with ECB-S certified Mauer keylock as standard
 - also available with various other electronic code or combination lock models
- Option for two locks
- Floor anchoring



Tested protection

- Fire protection for data and media records according to NT Fire 017 – 120 Diskette (fire protection for 120 minutes at temperatures of over 1045 °C), (PK-410 Data Safe NT Fire 017 – 90 Diskette)
- Burglary protection S1 according to European Standard EN 14450 (ECB-S)
- Manufactured in accordance with the ISO 9001:2000 quality management system



Design

- Wide range of models and flexible adjustment of the inside fittings allows a variety of uses
- Sealed double door structure for maximum security against fire, heat, magnetism and water
- Standard colour light grey, RAL 7035

Optional inside fittings



- Adjustable shelves
- Pull-out multi-purpose drawers with dividers



Internal dimensions of a multipurpose pull-out shelf:
PK-490 data safe 377 mm x 251 mm x 60 mm.
Other models 344 mm x 251 mm x 60 mm.

Burglaryproof PK-400 data safes

EN 14450 Grade S1 (ECB-S)
NT Fire 017 – 120 Diskette



Specifications

Model	PK-410 DATA SAFE	PK-420 DATA SAFE	PK-430 DATA SAFE	PK-440 DATA SAFE	PK-480 DATA SAFE	PK-490 DATA SAFE
External						
Height (mm)	680	1030	1380	1730	1730	1980
Width (mm)	670	670	670	670	1160	1220
Depth (mm)	580	580	580	580	580	580
Internal						
Height (mm)	390	740	1090	1440	1440	1690
Width (mm)	375	375	375	375	755	815
Depth (mm)	260	260	260	260	260	260
Volume (l)	39	73	108	142	284	361
Weight (kg)	170	230	300	380	625	725
Capacity (estimate), discs						
5.25" magneto-optical disc	95	185	280	415	830	920
CD/DVD	160	315	470	705	1405	1640
Zip drives	190	380	570	760	1515	2355
3.5" magneto-optical disc	390	905	1290	1810	3615	5505
Capacity (estimate), cartridges						
DLT	90	180	270	360	720	900
LTO, LTO Ultrium	110	220	325	435	865	1345
Exabyte 8 mm, Travan TR-4	195	390	585	780	1560	1820
AIT	310	615	920	1225	2450	3025
DAT	310	715	1020	1430	2860	3810
DDS	435	1010	1440	2020	4035	4995

Pull-out multipurpose drawer inner dimensions (mm): width 340 x depth 250 (models PK-410 – PK-480), width 375 x depth 250 (model PK-490).

Data safe capacity estimates are assuming adjustable shelves as internal accessories.

Individual data cartridge package sizes are manufacturer specific. More information from sales@kaso.fi.